

<p><b>1. DESCRIPTION</b></p> <p><b>Impa Wallpaper Sealer</b> is an excellent sealer for wallpaper. Yields a tough washable film which withstands repeated washing with water.</p> <p>May be added to all Emulsion paints at the rate of 1:5 litres of paint to improve the sealing and application properties, as well as wash ability, gloss and durability (particularly to interior waterbased paints).</p> <p><b>2. FEATURES</b></p> <ul style="list-style-type: none"> <li>• Water based, therefore cleaning is at low cost.</li> <li>• The acrylic binders impart excellent properties of weather and alkali resistance.</li> <li>• Ready for use.</li> <li>• The 100% acrylic binders ensure excellent adhesion to surfaces.</li> <li>• Excellent <b>flow</b> and <b>leveling</b> properties</li> </ul> <p><b>3. LIMITATIONS</b></p> <ul style="list-style-type: none"> <li>• Do not use as self-sealer coat under paint or emulsion finishes.</li> </ul> <p><b>4. SURFACE PREPARATION</b></p> <ul style="list-style-type: none"> <li>• Surfaces - must be clean and dry before applying this material. Wallpaper, in particular, must be free from grease and soil marks</li> </ul> <p><b>5. APPLICATION</b></p> <ul style="list-style-type: none"> <li>• Wallpaper – apply a single rush coat. The final appearance can be controlled by the amount of water added and as a guideline the following suggestions are made:  <u>Sheen</u>: add 2L of clean water 5L of Sealer.  <u>Semi-gloss</u>: add 1L of clean water to 5L of Sealer.  <u>High-gloss</u>: use undiluted.</li> </ul> <p>Note: Users unfamiliar with the above gloss terms should first paint a piece of waste wallpaper as a test area prior to applying the sealer to a whole wall. The most popular effect on wallpaper is a sheen finish.</p>	<p><b>TRANSLUCENT SURFACE COATINGS</b></p> <p><b>IMPA WALLPAPER SEALER</b></p> <p>ISSUED DATE : JUNE 2014, REV 1</p>														
	<p style="text-align: center;"><b>TECHNICAL DATA</b></p> <table border="1"> <tr> <td data-bbox="746 678 1102 741"> <i>Product Code</i>  <i>Colour</i> </td> <td data-bbox="1102 678 1519 741">                     SE1038                      Clear                 </td> </tr> <tr> <td data-bbox="746 741 1102 875"> <i>Appearance</i>  <i>Shelf life</i>  <i>Packaging</i>  <i>Flashpoint</i> </td> <td data-bbox="1102 741 1519 875">                     High-Gloss (undiluted)                      12 Months                      1L, 5L &amp; 20L                      Non flammable                 </td> </tr> <tr> <td data-bbox="746 875 1102 1037"> <i>Viscosity</i>  <i>S.G (weight)</i>  <i>Solids per volume</i>  <i>Solids per mass</i> </td> <td data-bbox="1102 875 1519 1037">                     50–60KU/23°C                      1,00-1,02Kg/L                      16 – 17%                      17 – 18%                 </td> </tr> <tr> <td data-bbox="746 1037 1102 1122"> <i>Practical Spreading rate (depending on porosity)</i>  <i>Recommended finishing coats.</i> </td> <td data-bbox="1102 1037 1519 1122">                     14m<sup>2</sup>/L per coat                      1 or 2 depending on finish required                 </td> </tr> <tr> <td data-bbox="746 1122 1102 1346" style="text-align: center;"> <p><b>DRYING TIME</b></p> <i>Touch dry time</i>  <i>Recoating Time</i>  <i>Full Cure</i> </td> <td data-bbox="1102 1122 1519 1346">                     1 Hour @ 23°C                      4Hours @ 23°C                      4-7 Days                 </td> </tr> <tr> <td data-bbox="746 1346 1102 1529" style="text-align: center;"> <p><b>APPLICATION</b></p> <i>Roller &amp; Brush (mohair preferred)</i>  <i>Spray</i> </td> <td data-bbox="1102 1346 1519 1529">                     Ready for use.                      Dilute with clean water if required                 </td> </tr> <tr> <td data-bbox="746 1529 1102 1659"> <i>Cleaning</i>  <i>Mixing</i> </td> <td data-bbox="1102 1529 1519 1659">                     Warm water and soap                      Stir until homogeneous                      Stir occasionally during use.                 </td> </tr> </table>	<i>Product Code</i> <i>Colour</i>	SE1038 Clear	<i>Appearance</i> <i>Shelf life</i> <i>Packaging</i> <i>Flashpoint</i>	High-Gloss (undiluted) 12 Months 1L, 5L & 20L Non flammable	<i>Viscosity</i> <i>S.G (weight)</i> <i>Solids per volume</i> <i>Solids per mass</i>	50–60KU/23°C 1,00-1,02Kg/L 16 – 17% 17 – 18%	<i>Practical Spreading rate (depending on porosity)</i> <i>Recommended finishing coats.</i>	14m <sup>2</sup> /L per coat 1 or 2 depending on finish required	<p><b>DRYING TIME</b></p> <i>Touch dry time</i> <i>Recoating Time</i> <i>Full Cure</i>	1 Hour @ 23°C 4Hours @ 23°C 4-7 Days	<p><b>APPLICATION</b></p> <i>Roller &amp; Brush (mohair preferred)</i> <i>Spray</i>	Ready for use. Dilute with clean water if required	<i>Cleaning</i> <i>Mixing</i>	Warm water and soap Stir until homogeneous Stir occasionally during use.
<i>Product Code</i> <i>Colour</i>	SE1038 Clear														
<i>Appearance</i> <i>Shelf life</i> <i>Packaging</i> <i>Flashpoint</i>	High-Gloss (undiluted) 12 Months 1L, 5L & 20L Non flammable														
<i>Viscosity</i> <i>S.G (weight)</i> <i>Solids per volume</i> <i>Solids per mass</i>	50–60KU/23°C 1,00-1,02Kg/L 16 – 17% 17 – 18%														
<i>Practical Spreading rate (depending on porosity)</i> <i>Recommended finishing coats.</i>	14m <sup>2</sup> /L per coat 1 or 2 depending on finish required														
<p><b>DRYING TIME</b></p> <i>Touch dry time</i> <i>Recoating Time</i> <i>Full Cure</i>	1 Hour @ 23°C 4Hours @ 23°C 4-7 Days														
<p><b>APPLICATION</b></p> <i>Roller &amp; Brush (mohair preferred)</i> <i>Spray</i>	Ready for use. Dilute with clean water if required														
<i>Cleaning</i> <i>Mixing</i>	Warm water and soap Stir until homogeneous Stir occasionally during use.														

## 6. PRECAUTIONS

- Application should be avoided in cold and moist weather conditions.
- **Do Not** apply the product at surface temperatures below 6°C (minimum of 2°C above dew point) and temperatures above 40°C
- **Do Not** apply if ambient temperature is less than 10°C or more than 40°C.
- **Do Not** apply if relative humidity temperature is less than 10°C or more than 85. °C
- When **Impa Wallpaper Sealer** is applied to textured surfaces or face brick: - be sure to reduce film built in such a way that white colouring does not take place. Application by brush is recommended.
- **Impa Wallpaper Sealer** is suitable for interior and exterior application
- **Impa Wallpaper Sealer** is not recommended for use over solvent based alkyd paints
- Keep out of reach of children
- Ensure good ventilation during application and drying
- In case of skin contact, wash with soap and water or a recognized skin cleaner
- Avoid contact with eyes – in case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.
- Harmful if swallowed. Do not induce vomiting. Seek medical attention
- Refer to Material Safety data Sheet for complete information

### Environmental Health & Safety Information

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: PROPYLENE ORETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapours and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN AND ANIMALS - DO NOT TAKE INTERNALLY.**

**Refer to Material Safety Data Sheet for additional health and safety information.**

**IN CASE OF FIRE:** Use foam, CO2, dry chemical, or water fog.

**SPILL** – Absorb with inert material and dispose of as specified under **Thinning/Clean-up**.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust.

### **DISCLAIMER**

*The technical information contained in this document are given in good faith and are meant to be used as a guideline by the specifier or user. Whilst we are confident about the quality of our products, we cannot accept any liability for the incorrect use or application of our products. Surface preparation forms an integral part of the scope of works and it is expected that the highest standards are maintained during surface preparation and application, to ensure that our products perform as intended. Always ensure to use the same product batch numbers, refrain from doing spot touch-ups and paint surfaces from corner to corner to prevent colour and sheen variance. As technology may change over time we reserve the right to change products to keep up with changes in raw materials or product trends without pre notice. Although we will always prevail to keep clients informed about changes to be made, but cannot bind ourselves to such notes Please ensure the use of the latest Technical Data Sheet.*

**Please note:** that all our latest Product Data Sheets and Material Safety Data Sheets are available for viewing on our website at [www.impa.co.za](http://www.impa.co.za). All information listed is owned or used under licence of Impa Paints and its related companies. © 2010 Lurama 149 (Pty) Ltd. All rights is reserved.